**3 YEAR Warranty**

HIK SERIES
P1.25 INDOOR LED DISPLAY

HIK series LED solutions deliver unrivalled versatility due to the variety of cabinet configurations available. Integrators specifying the HIK range have access to the broadest range of pixel pitch and aspect ratios options. Perfect for any internal space, these innovative Hisense LED modules include cable-less internal construction and full frontal access for ease of maintenance.

Highlights

High refresh rate
With uniform color scale and brightness, dynamic performance of LED display could restore the true scenes without any ripples.

Brightness nits
With an average 500 nits and 1,000 nits maximum brightness, the display panels can deliver amazingly vivid imagery anywhere during daytime and nighttime conditions.

Low brightness & High gray level
LED display could reveal more details, including layers and colors, than traditional displays do.

160° High viewing angle
The extra wide 160° viewing angle is a perfect fit for large groups of people that will view the displays from diverse angles while passing by.

High color calibration
LED display correction technology could uniformly lighten several hundred thousand LED lights, presenting a uniform display effect with the same brightness and color scale.

AOB Admixture on board
AOB Transparent glass on surface enhances the mixed light property with scratch resistance, water-proof & easy to clean.

Hisense

Specifications

HIK Series

Pixel Pitch	P1.25
LED Type	SMD1010
Thickness	53.7mm
Module Size (W H/mm)	240 x 270
Cabinet Dimension (W H/mm)	480 x 540 / 480 x 270 / 240 x 540
Cabinet Resolution	384 x 432
Cabinet Weight (kg/panel)	≤7kg (480 x 540) / ≤4kg (480 x 270) / ≤4kg (240 x 540)
Brightness (Nits)	500 (0-1000 Adjustable)
Contrast Ratio	7000:1
Maintanance	Front Access
IP Rating	IP50
Max Power Consumption (W/sqm)	≤650
Avg Power Consumption (W/sqm)	≤150
Viewing Angle	160°
Refresh Rate (Hz)	3840
Operating Enviroment	-10° to 40° / 10 to 90% Relative Humidity (non condensing)
Life Span	100,000 Hours

Display Dimensions

240 mm
540 mm
4:9

480 mm
540 mm
8:9

480 mm
270 mm
16:9

480 mm

47.6 mm